

TECHNICAL DATA SHEET

RUST VETO® 76-T SOLVENT-BASED RUST PREVENTIVE

RUST VETO® 76-T is especially designed to provide long-term protection of bearings and other precision machined steel components.

Up to 18 months indoor protection leaving a light oily film.

Applications

Application by dip or spray.

Recommendation For Use

Due to excellent alkaline resistance, RUST VETO® 76-T can be applied following the use of synthetic coolants and cleaners to effectively displace and separate these solutions.

Benefits

- Excellent low temperature stability
- High flash
- Water separating and water displacement characteristics

Health, Safety and Handling

Please consult the Safety Data Sheet (SDS) for information on storage, safe handling and disposal. The conditions or methods of handling, storage, use and disposal of the product are beyond our reasonable control - we assume no liability for any ineffectiveness of the product or any injury or damage, arising out of or in connection with these conditions.

Typical Physical Properties

PROPERTY	TYPICAL VALUE	UNIT
Appearance	Dark amber fluid	
Specific Gravity	0.833	
Pounds per Gallon	6.94	@ 60°F
Non volatile	17	%
Flash Point	200°	F
Humidity Test	30 days minimum	100% RH, 120°F (48.9°C)

All reasonable care has been taken to ensure this publication is accurate upon issue. Such information may be affected by changes subsequent to issue. This Technical Data Sheet is to be used solely for this product. Prior to any use, consult the Safety Data Sheet (SDS) for information on hazard risks and product use parameters. All liability and all warranties express or implied are hereby excluded as to product performance results, the accuracy of these data including any warranty of merchantability or fitness for any purpose. 21008000

