

TECHNICAL DATA SHEET

DIE SLICK® 77 EJECTOR PIN LUBRICANT

DIE SLICK® 77 will not gum or carbonize at extreme temperatures assuring continuous free movement of sliding parts.

Applications

DIE SLICK® 77 is a high temperature lubricant developed specifically for use on ejector pins and other moving parts of the die.

Health, Safety and Handling

Please consult the Safety Data Sheet (SDS) for information on storage, safe handling and disposal. The conditions or methods of handling, storage, use and disposal of the product are beyond our reasonable control - we assume no liability for any ineffectiveness of the product or any injury or damage, arising out of or in connection with these conditions. This product has a shelf life of 12 months, and it should be stored in a tightly sealed container in temperatures between 41°F (5°C) and 95°F (35°C). Do not freeze.

Benefits

- Forms a tenacious coating that resists leaching or carry through onto the metal being cast
- Provides excellent lubrication and protection
- Does not promote corrosion or pitting

Properties

PROPERTY	TYPICAL VALUE	UNIT
Appearance	Copper color	
Odor	Mild	
Bulk Density	8.0	lbs/gal
Flash Point	329	°F
Specific Gravity	0.95	

All reasonable care has been taken to ensure this publication is accurate upon issue. Such information may be affected by changes subsequent to issue. This Technical Data Sheet is to be used solely for this product. Prior to any use, consult the Safety Data Sheet (SDS) for information on hazard risks and product use parameters. All liability and all warranties express or implied are hereby excluded as to product performance results, the accuracy of these data including any warranty of merchantability or fitness for any purpose. 015636

