

TECHNICAL DATA SHEET

QH HYDROLUBRIC™ 123 B

SYNTHETIC HIGH WATER BASED HYDRAULIC FLUID

When used as recommended, QH HYDROLUBRIC™ 123 B is readily dispersible in water and will provide lubricating and rust preventive characteristics to metal surfaces.

Applications

QH HYDROLUBRIC™ 123 B is a synthetic water additive specifically designed to meet the needs of central water systems using reciprocating plunger, multi-stage centrifugal or multi-stage gear pumps.

Recommendation for Use

Recommended concentration is 2 - 5%.

Benefits

- Provides a film on metal surfaces that effectively reduces friction and provides protection against aqueous corrosion
- Product is compatible with conventional diluted soluble oils

Health, Safety and Handling

Please consult the Safety Data Sheet (SDS) for information on storage, safe handling and disposal. The conditions or methods of handling, storage, use and disposal of the product are beyond our reasonable control - we assume no liability for any ineffectiveness of the product or any injury or damage, arising out of or in connection with these conditions.

Properties

PROPERTY	TYPICAL VALUE	UNIT
Appearance	Dark blue fluid	
Viscosity at 100°F	32	SUS
Specific Gravity at 60°F	1.000	
pH	9.5	
Pour Point	32	°F
Freeze Point	32	
Flash Point	N/A	

All reasonable care has been taken to ensure this publication is accurate upon issue. Such information may be affected by changes subsequent to issue. This Technical Data Sheet is to be used solely for this product. Prior to any use, consult the Safety Data Sheet (SDS) for information on hazard risks and product use parameters. All liability and all warranties express or implied are hereby excluded as to product performance results, the accuracy of these data including any warranty of merchantability or fitness for any purpose 05123200

