

# TECHNICAL DATA SHEET

## QH EVERSOLVE™ VO 10

### VANISHING OIL

QH EVERSOLVE™ VO 10 is a solvent-dispersed preventative of the vanishing oil family specially formulated with a low-odor solvent.

#### Applications

The solvent will evaporate leaving a minimal film on the strip that imparts excellent corrosion protection.

#### Fluid Maintenance

QH EVERSOLVE™ VO 10 is used as received. It should not be diluted with any type of solvent or oil. Dilution will significantly reduce its performance and quality. Concentration control is not an issue with this product because it is used as received.

#### Health, Safety and Handling

Please consult the Safety Data Sheet (SDS) for information on storage, safe handling and disposal. The conditions or methods of handling, storage, use and disposal of the product are beyond our reasonable control - we assume no liability for any ineffectiveness of the product or any injury or damage, arising out of or in connection with these conditions. This product has a shelf life of 6 months, and it should be stored out of direct sunlight in temperatures between 40°F (4°C) and 110°F (43°C).

#### The Benefits

- Leaves a slight non-oily film that imparts corrosion protection
- Will not turn tacky or gummy and completely dissipates in 30 - 45 minutes
- Will not stain ferrous or nonferrous parts
- Contains a low odor solvent

#### Properties

PROPERTY	TYPICAL VALUE	UNIT
Appearance	Clear light amber	
Pounds per gallon at 60°F	6.716	lbs/gal
Coverage per Gallon	1800	ft <sup>2</sup>
Flash Point via TCC	72   162	°C   °F
Dry Time	30-45	mins
Film Thickness	0.25	mils

PERFORMANCE TESTS	RESULTS
JAN H-792 Cabinet Galvanize	8 - 12 days
Galvalume	20 - 25 days
Cold Rolled Steel	11 - 15 days
Stack Stain Test Galvanize / Galvalume / Cold Rolled Steel	No rust or stain

All reasonable care has been taken to ensure this publication is accurate upon issue. Such information may be affected by changes subsequent to issue. This Technical Data Sheet is to be used solely for this product. Prior to any use, consult the Safety Data Sheet (SDS) for information on hazard risks and product use parameters. All liability and all warranties express or implied are hereby excluded as to product performance results, the accuracy of these data including any warranty of merchantability or fitness for any purpose. 013510-10

