

# TECHNICAL DATA SHEET

## RUST VETO® 4240

### SOLVENT-BASED RUST PREVENTIVE

RUST VETO® 4240 is a solvent-based rust preventive that rapidly displaces and separates water. Up to 12 months corrosion protection leaving a dry-to-touch film. GM approval.

#### Applications

Apply by immersion.

#### Recommendation For Use

Product is used neat.

#### Benefits

- Excellent humidity rust protection
- Easily removed
- For use with all metals
- Barium-free
- Thin film protects your parts without excessive carry-off which reduces usage and cost.

#### Health, Safety and Handling

Please consult the Safety Data Sheet (SDS) for information on storage, safe handling and disposal. The conditions or methods of handling, storage, use and disposal of the product are beyond our reasonable control - we assume no liability for any ineffectiveness of the product or any injury or damage, arising out of or in connection with these conditions.

#### Typical Physical Properties

PROPERTY	TYPICAL VALUE
Appearance	Clear amber
Non-Volatile	6
Specific Gravity	0.79
Copper Corrosion	1a
Flash Point	195°F
Film Thickness	0.036
Humidity ASTM D-1748	Passes 30+ days
Water Separation	Passes

All reasonable care has been taken to ensure this publication is accurate upon issue. Such information may be affected by changes subsequent to issue. This Technical Data Sheet is to be used solely for this product. Prior to any use, consult the Safety Data Sheet (SDS) for information on hazard risks and product use parameters. All liability and all warranties express or implied are hereby excluded as to product performance results, the accuracy of these data including any warranty of merchantability or fitness for any purpose. 21424000

